

Commercial Duo Series Pedestal

Innovativeness

- One charger with two output sockets
- Business use with intelligent App control
- Vandal resistant and anti-corrosion

Intelligent Control

- Ethernet/4G/Wi-Fi communication all supported
- OCPP communication protocol with CMS
- Intelligent operation by App and cashless payment

Flexible Option

- App operation or RFID authentication or plug and play
- Customization with different color painting

Secure and Safe

- RCD Type A and 6mA DC residual current protection
- MID certified energy meter with accurate measurement

Twin Series Pedestal

Datasheet	Model	BUSINESS DUO 2x11kW	BUSINESS DUO 2x22kW
Input	Power Supply	3P+N+PE	3P+N+PE
	Rated Voltage	400V AC	400V AC
	Rated Current	32A	64A
	Frequency	50/60Hz	50/60Hz
Output	Output Voltage	400V AC	400V AC
	Maximum Current	3x16A	3x32A
	Rated Power	2x1 1kW	2x2 2kW
User Interface	Charge Connector	Type 2 socket	
	Enclosure	Galvanized steel	
	Left/Right Panel	Temper glass	
	LED Indicator	Green/Yellow/Red	
	LCD Display	2.7" black & white screen	
	RFID Reader	Mifare ISO/IEC 14443 A	
	Start Mode	Plug&Play/RFID card/App	
Communication	Emergency Stop	No	
	Wi-Fi	Yes	
	Ethernet	Yes	
	3G/4G	Yes	
Safety	OCP	OCPP 1.6 Json (OCPP 2.0 optional)	
	Energy Meter	MID certified	
	RCD	30mA Type A + 6mA DC	
	Ingress Protection	IP54	
	Impact Protection	IK08	
	Electrical Protection	Over current protection, Residual current protection, Short circuit protection, Ground protection, Surge protection, Over/Under voltage protection, Over/Under frequency protection, Over/Under temperature protection	
	Certification	CE	
	Certification Standard	EN/IEC 61851-1: 2017, EN/IEC 61851-21-2: 2018	
Environment	Warranty	2 years	
	Installation	Floor-stand	
	Work Temperature	-30°C~+50°C	
	Work Humidity	5%~95%	
Package	Work Altitude	<2000m	
	Product Dimension	1200*290*230mm (H*W*D)	
	Package Dimension	1320*480*430mm (L*W*H)	
	Net Weight	25.5kg	
	Gross Weight	45kg	
External Package	Wood case		