




## Safe and convenient HV battery system for PV power back-up and energy autonomy

- ✓ Maximised power back-up
- ✓ Highest safety standards
- ✓ Smart and efficient operation
- ✓ High battery cycle stability

Ideal for smart energy management and back-up optimisation, high-voltage (HV) battery system Lynx Home F PLUS+ is a perfect match for residential solar systems. The stackable, self-detecting battery modules make the system especially easy to install, while the reliable lithium iron phosphate (LFP) battery cell technology ensures maximum safety. Lynx Home F PLUS+ offers a wide capacity range from 6.6kWh to 16.4kWh, is compliant to the advanced battery safety standard VDE 2510-50 and is compatible with Power BH/EH/BT/ET inverters.

-  Reliable LFP battery cell
-  Up to 8 towers in parallel (131kWh)
-  Remote diagnosis and update via inverter



# Lynx Home F PLUS+ Series

Technical Data	LX F6.6-H	LX F9.8-H	LX F13.1-H	LX F16.4-H
Usable Energy (kWh) <sup>*1</sup>	6.55	9.83	13.10	16.38
Battery Module	LX F3.3-H: 102.4V 3.27kWh			
Number of Modules	2	3	4	5
Cell Type	LFP (LiFePO4)			
Nominal Voltage (V)	204.8	307.2	409.6	512.0
Operating Voltage Range (V)	182.4 ~ 230.4	273.6 ~ 345.6	364.8 ~ 460.8	456.0 ~ 576.0
Nominal Dis- / Charge Current (A) <sup>*2</sup>	25			
Nominal Power (kW) <sup>*2</sup>	5.12	7.68	10.24	12.80
Operating Temperature Range (°C)	Charge: 0 ~ +50; Discharge: -20 ~ +50			
Relative Humidity	0 ~ 95%			
Max. Operating Altitude (m)	2000			
Communication	CAN			
Weight (kg)	115	158	201	244
Dimensions (W x H x D mm)	600 x 610 x 380	600 x 765 x 380	600 x 920 x 380	600 x 1075 x 380
Ingress Protection Rating	IP55			
Mounting Method	Grounded			
Standard and Certification	Safety	IEC62619, IEC62040, VDE2510-50, CEC		
	EMC	CE, RCM		
	Transportation	UN38.3		

\*1: Test conditions, 100% DOD, 0.2C charge & discharge at +25 ±2°C for battery system at beginning life. System Usable Energy may vary with different Inverter.

\*2: Nominal Dis- / Charge Current and power derating will occur related to Temperature and SOC.

\*: All product specifications are subject to change without notice.

\*: Please visit Power website for the latest certificates.